

SC-324-XDZ



FEATURES

4MP Motorized Vari-focal EXIR Turret, Exterior

- 4 Megapixel (2688 × 1520) Resolution
- Full HD 4MP real-time video
- True WDR & 3D DNR & BLC
- EXIR illuminator up to 100ft.
- IP67, IK10
- PoE
- H.265

Specifications	
Model Number	SC-324-XDZ
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @ F1.2, AGC ON, 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8mm - 12mm @ F1.6, angle of view: 98° to 28°
Angle adjustment	Pan: 0° ~ 355°, tilt 0° ~ 75°
Digital noise reduction	3D DNR
Wide Dynamic Range	True WDR, 120db
Backlight compensation	Yes, zone configurable
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
Audio input output	Yes
Bit rate	32 Kbps ~ 16 Mbps

Specifications	
Dual stream	Yes
Max. image resolution	2688 x 1520
Frame rate	20fps (2688 × 1520)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Storage	Micro SD Card up to 128 GB
Network storage	NAS
Alarm I/O	1/1
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 10W (12.5W with ICR on)
Ingress protection	IP67, IK10
EXIR range	up to 100ft
Dimensions	Ø5.35"x5.73"
Weight	2.6lbs.
Pendant Mount	PC135
Wall Mount	WML+PC135
Corner Mount	DS-1276ZJ
Pole Mount	DS-1275ZJ