

mi-MCT385 Specification

**WIRELESS
WISDOM**



mi-MCT385

The mi-MCT385 is an IP65 handset compliant with the miMCB8663W system, which targets the industrial, hospital, hotel, secure and lonely worker verticals.



Call TOLL FREE 1-800-668-3402

sales@nsidistribution.com

27 Armthorpe Road, Brampton, ON, L6T 5M4 Canada

Toronto
1-800-668-3402

Vancouver
1-877-785-0153

Montreal
1-800-361-7793

Markham
1-866-574-0123

Calgary
1-866-680-0123

Edmonton
1-877-701-0123

Barrie
1-833-466-1669



MAIN HANDSET FEATURES

- HD audio support (G.722)
- 2" TFT display, 176 x 220
- IP65 compliant
- Ruggedized design
- Dedicated Alarm key on handset top
- Pull cord support
- Man-down support
- Ambient noise reduction
- Optional Bluetooth for headset
- Optional LF (125kHz) receiver for positioning
- Micro SD-card support for fast handset exchange
- Single SKU for WorldWide deployment

Wireless



BOX CONTENT

- 1 MCT385 handset
- 1 Lith-Ion battery
- 1 battery cover
- 1 beltclip
- 1 table charger
- 1 AC adaptor
- 1 User guide
- 1 Safety sheet

TECHNICAL SPECIFICATIONS

AUDIO

- G722 codec for HD audio
- G726 codec for narrow band audio
- HD audio speakerphone
- HAC compliant (TIA-1083)
- Loudspeaker volume: >=100dBspl
- Speakers insensitive to metal swarf

DISPLAY

- 2" 176 x 220 pixels 64k TFT display
- 3 color MWI LED)
- min. 20 languages supported

KEYPAD

- 28 keys total including 5-way navi-key
- 3 soft keys, 3 side keys
- 1 alarm key on top
- ON- and OFF- hook keys
- IMD technology, with backlight

HEADSET OPTIONS

- 3.5mm wired headset, Iphone compliant
- Optional Bluetooth

RINGER

- 20 polyphonic melodies, 6 levels
- Volume control, Silent ringer
- Alerting volume, adjustable (low battery, low coverage)
- Vibrator

DECT

- Frequency Bands:
 - ◊ 1880 - 1900MHz (EU)
 - ◊ 1910 - 1930MHz (LATAM)
 - ◊ 1910 - 1920MHz (BRAZIL)
 - ◊ 1920 - 1930MHz (US)
- Range:
 - ◊ 1Indoor: 50m
 - ◊ Outdoor: 300m
- Power levels: 4
- Two Antennas, fast diversity
- Encryption supported
- 10 system registrations

CALL FEATURES

- Call list with 50 entries (All, received, outgoing, missed)
- Speed dial
- Central phonebook support (multiple LDAP server)
- Local phonebook with 250 entries (3 numbers/names)
- Date and time in idle display
- DND and CFx enable/disable from handset
- Call waiting indication
- Conference call, Call Swap support

MESSAGING

- SMS messaging, max length 200 chars
- Alarm generation from key, ManDown or Pull cord
- Alarms list with colors
- Storage: 35000 chars shared between SMS and Alarms

SIZE AND WEIGHT

- Size: 152 x 48 x 28mm
- Weight: 175g

POWER PERFORMANCE

- Talk time 17h(NB), 12h(WB)
- Standby time 200 hours
- Battery type: Lith Ion
- Cradle charging time: 6 hrs
- USB charging time TBD
- Adaptor plugs: EU/ US/ AUS/UK

ENVIRONMENTAL CONDITIONS

- IP65 compliant
- Shock proof
- Enhanced ESD: 8kV contact and 16kV air
- Operating conditions: -10 to 55 degrees

LIABILITY SPEC

- Drop height: 2m on concrete floor
- Tumble test: 1000 x 0.5m
- Keypad lifetime: 100,000 presses
- Keypad abrasion: 70 RCA cycles

APPROVALS

- EU/ US/ CA/AUS

Call TOLL FREE 1-800-668-3402

sales@nsidistribution.com

27 Armthorpe Road, Brampton, ON, L6T 5M4 Canada

Toronto
1-800-668-3402

Vancouver
1-877-785-0153

Montreal
1-800-361-7793

Markham
1-866-574-0123

Calgary
1-866-680-0123

Edmonton
1-877-701-0123

Barrie
1-833-466-1669

