



RMC-66A

SPECS AND WARRANTY

RMS Power @ 8 ohms	25 watts x 12
RMS Power @ 4 ohms	50 watts x 12
RMS Power @ 8 ohms Bridge Mode	100 watts x 6
S/N Ratio	>85dB A Weighted
THD	<0.1%
Frequency Response	20Hz - 20kHz
Input Impedance	>47 K Ohms
Input Sensitivity	250mv
Amplifier Protection	Overload, Short Circuit & Thermal
Trigger Systems ON Voltage	DC + 12V
Trigger External Mute Voltage	DC + 12V
Infrared Frequency	38kHz
Input Connectors	Stereo RCA, 3.5mm
Output Connectors	Terminal Block, Stereo RCA, 3.5mm
Ethernet	10/100Mbps RJ45 Connector
Dimensions: Imperial / Metric	W- w/rack kit 19"/482.6mm W- no/rack kit 17"/430mm H - 3.5"/89mm D - 16.4"/416mm
Weight: Imperial / Metric	25lbs (11kg)
Warranty	5 Years

Contact Information:
Rave Technology
4100 East Baldwin Road
Holly, Michigan, 48442 USA
Tel: 866-303-2629
contact@ravetechnology.com
www.ravetechnology.com

Warranty:
Rave Technology products are warranted to be free from defects in workmanship and materials for a period of Five (5) years from the date of purchase without charge for parts or labor. This warranty does not apply to units that have been subject to misuse, abuse, neglect or improper installation, and does not apply to repairs or alterations made by unauthorized personnel. This warranty specifically excludes responsibility for consequential damage. Retention of your original bill of sale is required to obtain service under the terms of this warranty.

© 2020 Rave Technology. All rights reserved.
All trademarks are the property of their respective owners. Specifications are subject to change without notice.