

SC-326D-OD4Z



FEATURES

IVMS HD 4-in-1 5MP Motorized Vari-Focal IR Dome, Exterior

- 5MP HD 4-in-1 Video Output (TVI/CVI/AHD/CVBS)
- True Day/Night
- 2.7 - 13.5mm Motorized vari-focal lens
- OSD menu, 3D DNR, Smart IR
- Up to 120 ft IR distance
- IP67 weatherproof & IK10 Vandal Proof
- DWDR
- Dual Voltage 12VDC/24VAC

Specifications

Model Number	SC-326D-OD4Z
Image Sensor	5MP CMOS image sensor
video FORMAT	PAL / NTSC
Effective Pixels	2560(H)*1944(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/30s to 1/50,000s
Lens	2.7-13.5mm @ F1.2, Angle of view: 95.7° - 29.1°
Angle Adjustment	Pan: 0 - 355°, Tilt: 0 - 75°, Rotate: 0-355°
Day & Night	ICR
Wide dynamic range	DWDR
Video Frame Rate	2560 x 1944@20fps
HD Video Output	1 BNC output (TVI/CVI/AHD/CVBS)

Specifications	
CVBS Output	Support
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/Auto
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC, 24 VAC
Power Consumption	Max. 6W
Ratings	IP67, IK10
IR Range	Up to 120 ft
Dimensions	φ145.3 × 124.2 mm (φ7.1" × 4.89")
Weight	1.44lbs
Wall Mount	SC-273ZJ-140B
Pendant Mount	SC-271ZJ-140
Pole Mount	SC-275ZJ
Corner Mount	SC-276ZJ